

TL-EX-BR-X1-X2-X3-X4-X5

Specifications / Dimensions

Light Source	:	SMD Power LED
Input Voltage	:	90-305 VAC
Optional Input Voltage	:	24 VAC / VDC
Power Range	:	3 - 250 W
Power Factor	:	≥ 95
Luminaire Efficiency	:	135-165 lm/W
Color Temperature	:	2700-6500 Kelvin
Lifespan	:	Up to 100,000 hours
Housing	:	Special Aluminium Alloy
Operating Temp	:	-40°C - +50°C
Cooling	:	Specially Designed Cooling Panel
Light Distribution	:	30° - 60° - 90° - 120° Or optional
Optic Interface	:	Tempered Glass
Diffused Optic	:	Optional
Protection Class	:	IP67
Impact Resistance Class	:	Aluminum Housing: IK10 & Glass : IK10
Mounting	:	Wall , Ceiling , Pole , Mast , Conduit
Optional Mounting	:	Portable , Universal Kit , Angled Pole
Optional	:	Wire Guard 1 Input 2 Output Electrical Connection Emergency Kit (1-3 hours) Advanced Control / Dali - Dali Traceable Kit
Diameter	:	260 mm
Height	:	290 mm
Weight	:	11 kg