

TL-EX-TLL-XXX-XXX-XXX

Specifications / Dimensions

Light Source	:	SMD High Power LED
Input Voltage	:	198 - 264 V AC 50 Hz
Optional Input Voltage	:	24 VAC / VDC
Power Range	:	5 - 110 W
Power Factor	:	≥ 95
Luminaire Efficiency	:	135-165 lm/W
Color Temperature	:	2700-6500 Kelvin
Lifespan	:	Up to 100.000 hours
Housing	:	Special Aluminium Alloy
Operating Temp	:	-40°C - +50°C
Cooling	:	Specially Designed Cooling Panel
Light Distribution	:	30° - 60° - 90° - 120° Or optional
Optic Interface	:	Tempered Glass
Diffused Optic	:	Optional
Protection Class	:	IP67
Impact Resistance Class	:	Aluminum Housing: IK10 & Glass : IK07 - IK08 - IK09 Options
Mounting	:	Wall , Ceiling , Pole Mounting Kit
Optional Mounting	:	Portable ,Magnetic Portable , Universal Kit
Optional	:	Wire Guard Trough Wiring System Emergency Kit (1-3 hours) Advanced Control / Dali - Dali Traceable Kit
Lenght	:	425 mm
Width	:	88 mm
Height	:	105 mm
Weight	:	4,5 kg