

TL-EX-75 LNR-X1-1M-75W

Specifications / Dimensions

Light Source	: SMD Power LED
Input Voltage	: 198 - 264 V AC 50 Hz
Optional Input Voltage	: 90-305 VAC (or 24 V AC / VDC = 45W)
Power Range	: 20-75 W
Power Factor	: ≥ 95
Luminaire Efficiency	: 135-165 lm/W
Color Temperature	: 2700-6500 Kelvin
Lifespan	: Up to 100.000 hours
Housing	: Special Aluminium Alloy
Operating Temp	: -40°C - +50°C / +70°C
Cooling	: Specially Designed Cooling Panel
Light Distribution	30° - 60° - 90° - 120° - 140° - 30°x70° - 60°x90° - 90°x120° - 40°x130° - 70°x145 - 80°x155°
Optic Interface	: PC Block Lens
Protection Class	: IP66 & IP67
Impact Resistance Class	: Aluminum Housing: IK10 & Lens : IK09
Mounting	: Wall , Ceiling , Pole , Mast
Optional Mounting	: Portable ,Universal Kit
Optional	Wire Guard Trough Wiring Emergency Kit (1-3 hours) Advanced Control / Dali - Dali Traceable Kit
Lenght	: 329 mm
Width	: 143 mm
Height	: 167 mm
Weight	: 2 kg