

TL-EX-LNR-X1-3M- 225W

Specifications / Dimensions

Light Source	:	SMD Power LED
Input Voltage	:	198 - 264 V AC 50 Hz
Optional Input Voltage	:	90-305 VAC (or 24 V AC / VDC = 135W)
Power Range	:	20 - 225 W
Power Factor	:	≥ 95
Luminaire Efficiency	:	135-165 lm/W
Color Temperature	:	2700-6500 Kelvin
Lifespan	:	Up to 100.000 hours
Housing	:	Special Aluminium Alloy
Operating Temp	:	-40°C - +50°C / +70°C
Cooling	:	Specially Designed Cooling Panel
Light Distribution	:	30° - 60° - 90° - 120° - 140° - 30°x70° - 60°x90° - 40°x130° - 70°x145 - 80°x155°
Optic Interface	:	PC Block Lens
Protection Class	:	IP66 & P67
Impact Resistance Class	:	Aluminum Housing: IK10 & Lens : IK09
Mounting	:	Wall , Ceiling , Pole , Mast
Optional Mounting	:	Portable ,Universal Kit
Optional	:	Wire Guard Trough Wiring Emergency Kit (1-3 hours) Advanced Control / Dali - Dali Traceable Kit
Lenght	:	919 mm
Width	:	143 mm
Height	:	167 mm
Weight	:	6 kg